

Listing of and Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Cancelled).

2. (Currently Amended) ~~The steer axle and suspension assembly of claim 1~~

A steer axle and suspension assembly for a vehicle having a frame including first and second longitudinal frame rails extending parallel to one another, said assembly comprising:

a steer axle assembly including

an axle beam defining a first bore at a first longitudinal end and a second bore at a second longitudinal end, said axle beam extending transverse to said first and second frame rails;

a first kingpin disposed within said first bore in said axle beam;

a second kingpin disposed within said second bore in said axle beam;

a first steering knuckle rotatably supported on said first kingpin; and,

a second steering knuckle rotatably supported on said second kingpin; and,

a suspension including

a suspension member connected to said frame at a first end and to said steer axle assembly at a second end; and,

a first suspension arm connected to said frame at a first end and to said steer axle assembly at a second end at a location outboard of said first and second frame rails, said first suspension arm extending longitudinally at an angle relative to said first and second frame rails

wherein said second end of said first suspension arm is mounted on said axle beam.

3. (Cancelled).

4. (Currently Amended) ~~The steer axle and suspension assembly of claim 1~~

A steer axle and suspension assembly for a vehicle having a frame including first and second longitudinal frame rails extending parallel to one another, said assembly comprising:

a steer axle assembly including

an axle beam defining a first bore at a first longitudinal end and a second bore at a second longitudinal end, said axle beam extending transverse to said first and second frame rails;

a first kingpin disposed within said first bore in said axle beam;

a second kingpin disposed within said second bore in said axle beam;

a first steering knuckle rotatably supported on said first kingpin; and,

a second steering knuckle rotatably supported on said second kingpin; and,

a suspension including

a suspension member connected to said frame at a first end and to said steer axle assembly at a second end; and,

a first suspension arm connected to said frame at a first end and to said steer axle assembly at a second end at a location outboard of said first and second frame rails, said first suspension arm extending longitudinally at an angle relative to said first and second frame rails

wherein said second end of said first suspension arm is mounted on said first steering knuckle.

5. (Currently Amended) The steer axle and suspension assembly of claim 1 wherein said suspension member comprises a second suspension arm.

6-9. (Cancelled).

10. (Currently Amended) The steer axle and suspension assembly of claim ~~4~~ 2 wherein said second end of said suspension member is connected to said steer axle assembly at a location outboard of said first and second frame rails, said suspension member extending longitudinally at an angle relative to said first and second frame rails.

11. (Original) The steer axle and suspension assembly of claim 10 wherein one of said suspension member and said first suspension arm is connected to said frame forward of said axle beam and another of said suspension member and said first suspension arm is connected to said frame rearward of said axle beam.

12. (Currently Amended) The steer axle and suspension assembly of claim 10 wherein said second end of said suspension member and said second end of said first suspension arm are both mounted on ~~the same one of~~ said axle beam, ~~said first kingpin and said first steering knuckle.~~

13. ~~The steer axle and suspension assembly of claim 10~~
A steer axle and suspension assembly for a vehicle having a
frame including first and second longitudinal frame rails
extending parallel to one another, said assembly comprising:
a steer axle assembly including
an axle beam defining a first bore at a first
longitudinal end and a second bore at a second longitudinal end,
said axle beam extending transverse to said first and second
frame rails;
a first kingpin disposed within said first bore in
said axle beam;
a second kingpin disposed within said second bore in
said axle beam;
a first steering knuckle rotatably supported on said
first kingpin; and,
a second steering knuckle rotatably supported on said
second kingpin; and,
a suspension including
a suspension member connected to said frame at a first
end and to said steer axle assembly at a second end; and,
a first suspension arm connected to said frame at a
first end and to said steer axle assembly at a second end at a
location outboard of said first and second frame rails, said
first suspension arm extending longitudinally at an angle
relative to said first and second frame rails
wherein said second end of said suspension member is
connected to said steer axle assembly at a location outboard of
said first and second frame rails, said suspension member
extending longitudinally at an angle relative to said first and
second frame rails and
wherein one of said second end of said suspension member
and said second end of said first suspension arm is mounted to
one of said axle beam, said first kingpin and said first steering
knuckle and another of said second end of said suspension member
and said second end of said first suspension arm is mounted to

another of said axle beam, said first kingpin and said first steering knuckle.

14-20. (Cancelled).

21. (New) The steer axle and suspension assembly of claim 4 wherein said suspension member comprises a second suspension arm.

22. (New) The steer axle and suspension assembly of claim 4 wherein said second end of said suspension member is connected to said steer axle assembly at a location outboard of said first and second frame rails, said suspension member extending longitudinally at an angle relative to said first and second frame rails.

23. (New) The steer axle and suspension assembly of claim 22 wherein one of said suspension member and said first suspension arm is connected to said frame forward of said axle beam and another of said suspension member and said first suspension arm is connected to said frame rearward of said axle beam.

24. (New) The steer axle and suspension assembly of claim 22 wherein said second end of said suspension member and said second end of said first suspension arm are both mounted on said first steering knuckle.

25. (New) The steer axle and suspension assembly of claim 13 wherein said suspension member comprises a second suspension arm.

26. (New) The steer axle and suspension assembly of claim 13 wherein one of said suspension member and said first suspension arm is connected to said frame forward of said axle beam and another of said suspension member and said first suspension arm is connected to said frame rearward of said axle beam.